



Workgroup Server 9150



Workgroup Server 9150

Ordering Information

Workgroup Server 9150 (16MB/2 x 1GB)

Order No. M3272LL/A

- Workgroup Server 9150 with 16MB of RAM, 512K of level-2 cache, two 1GB hard disk drives, CD-ROM drive, DDS-2 DAT drive, CD-ROM drive, and 1.4MB Apple SuperDrive floppy disk drive
- Mouse
- System 7 software
- Retrospect Remote software
- Apple RAID software
- Complete setup, learning, and reference documentation
- Limited one-year warranty

Workgroup Server 9150 with AppleShare (16MB/2 x 1GB/AppleShare)

Order No. M3357LL/A

- Identical to above configuration, with the addition of AppleShare software version 4.0.2

Workgroup Server 9150 (24MB/2 x 2GB)

Order No. M3183LL/A

- Workgroup Server 9150 with 24MB of RAM, 512K of level-2 cache, two 2GB hard disk drives, CD-ROM drive, DDS-2 DAT drive, CD-ROM drive, and 1.4MB Apple SuperDrive floppy disk drive

Workgroup Server 9150 Logic Board Upgrade

Order No. M3262LL/A

- Upgrades a Macintosh Quadra 900 or 950 to a Workgroup Server 9150.
- Includes 8MB of RAM, Apple RAID software; AppleShare software must be purchased separately. Additional RAM required.

Note: This upgrade is not for the Workgroup Server 95.

Macintosh Memory Expansion Kits

Order No. M1507LL/A

- 4MB (1-4MB SIMM)

Order No. M1508LL/A

- 8MB (1-8MB SIMM)

Order No. M3372LL/A

- 16MB (1-16MB SIMM)

Order No. M3373LL/A

- 32MB (1-32MB SIMM)

Note: SIMMs must be installed in pairs by authorized Apple service provider. The Workgroup Server 9150 has four pairs of SIMM sockets, some of which may be occupied.

Apple Token Ring NB/c Card (7-inch)

Order No. M1769Z/A

Apple Token Ring 4/16 Card (12-inch)

Order No. M0415LL/B

Product specifications are subject to change. Check with your Apple reseller for the most current information about product specifications and configurations.

Technical Specifications

Microprocessor

- PowerPC 601 RISC microprocessor running at 80 MHz
- Integrated floating-point unit and 32K on-chip cache
- 512K level-2 cache

Memory

- 16MB or 24MB of RAM
- Can be expanded to up to 264MB of RAM

Drives

- Two 1GB or 2GB Apple hard disk drives
- One DDS-2 DAT drive (4MB uncompressed, 10-14GB compressed)
- One AppleCD 300i Plus CD-ROM drive (up to 342K-per-second streaming data-transfer rate)
- One Apple SuperDrive 1.4MB floppy disk drive that uses high-density floppy disks and reads, writes, and formats Macintosh, Windows, MS-DOS and OS/2 disks

Apple RAID Software¹

- Disk mirroring (RAID Level 1) for redundancy and reliability; stores the same current data on two different disks
- Disk striping (RAID Level 0) for better performance; stores one file in several small chunks across several disk drives; does not provide data redundancy

Note: For information on hard disk drives and arrays that are compatible with Apple RAID software, call Apple customer service at 1-800-SOS-APPLE.

Displays

- Supports up to 14-inch Apple displays at 32,768 colors, and 16- and 17-inch Apple displays at 256 colors
- Supports most third-party displays as well as VGA and SVGA monitors

Video support

- Built-in DRAM display support

Interfaces

- Four NuBus expansion slots
- One processor-direct slot
- One Apple Desktop Bus (ADB) port for a keyboard, mouse, and other device
- AAUI-15 Ethernet connector
- Two DMA serial (RS-232/RS-422) ports compatible with LocalTalk
- Dual-channel, high-speed asynchronous SCSI DMA interface; one supports up to seven external SCSI devices, the other supports up to seven internal SCSI devices (for a total of 14)
- 16-bit stereo sound input and output ports
- DB-15 video port for display support

Networking

- Built-in Ethernet
- Two serial ports for LocalTalk

Clock/calendar

- Custom integrated circuit with long-life lithium battery

Disability access

- Easy Access and visible beep included with system software to provide alternative input and output devices for people with disabilities

Electrical requirements

- Line voltage: 100 to 240 volts AC, RMS single phase, automatically configured
- Frequency: 50 to 60 Hz, single phase
- Power: 303 W maximum, not including display

ADB power requirements

- Maximum current draw for all ADB devices: 500 mA (a maximum of three ADB devices is recommended)
- Mouse draws 10 mA
- Keyboard draws 25 to 80 mA (varies with keyboard model used)

Keyboard and mouse

- Supports ADB keyboards with numeric keypads
- ADB Mouse II included

Size and weight

- Height: 18.6 in. (47.3 cm)
- Width: 8.9 in. (22.4 cm)
- Depth: 20.6 in. (52.3 cm)
- Weight: 36.8 lbs. (16.7 kg) (varies based on internal devices installed)

Operating environment

- Operating temperature: 50° to 95° F (10° to 35° C)
- Storage temperature: -40° to 116.6° F (-40° to 116.6° C)
- Relative humidity: 20% to 80% noncondensing
- Maximum altitude: 10,000 ft. (3,048 m)

Regulatory approval

- FCC Class A

¹ Available Summer of 1994

Apple Computer, Inc.

1 Infinite Loop
Cupertino, CA 95014
(408) 996-1010
TLX 171-576

© 1994 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, AppleShare, AppleTalk, AU/X, LocalTalk, and Macintosh are trademarks of Apple Computer, Inc., registered in the U.S.A. and other countries. AppleCD, Apple Desktop Bus, AppleSearch, Apple SuperDrive, Power Macintosh, and PowerShare are trademarks of Apple Computer, Inc. MS-DOS is a registered trademark of Microsoft Corporation. NuBus is a trademark of Texas Instruments. PowerPC is a trademark of International Business Machines Corporation, used under license therefrom. Retrospect and Retrospect Remote are registered trademarks of Dantz Development Corporation. Mention of non-Apple products or services is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, and warranties, if any, take place directly between the vendors and the prospective users.
April 1994. Product specification information as of April 1, 1994. Product specifications may vary depending on particular configuration or region in which purchased, and are subject to change without notice. Please see your Apple reseller for the most current information about product specifications and configurations. Printed in the United States of America.
L00686A